



## 3M™ 2800 Series Safety Eyewear

### Product Description

The 2800 series of safety eyewear has been designed to be worn over prescription spectacles. Products include both pantoscopic adjustment (angle of the lens frame to the temple) and adjustable temple arm length (4 fixed positions). The temple tips also include eyelets to allow easy attachment of a lanyard. Three lens variants are available: Clear, Amber and Weldingshade

### Product Range

2800 Over Spectacles PC Clear AS  
2802 Over Spectacles PC Amber AS  
2805 Over Spectacles PC Weldingshade AS

### Intended Use

These products are intended for protection against high speed particles at low energy (F) at extreme temperature conditions, -5°C and +55°C, (T) in accordance with EN166:2001.

A number of lens options are available for a variety of different applications:

- **Clear** – Good colour recognition and excellent UV protection
- **Amber** – Enhanced contrast in low light condition e.g. surface inspection
- **Weldingshade** – Offers protection for certain welding applications

### Key Features

- Optical class 1 lens suitable for prolonged use
- Offers excellent protection against UV radiation
- Designed to be worn over prescription eyewear
- Adjustable temple features
- Easy attachment to lanyards

### Applications

These products can be used in a wide range of applications including:

- Certain welding applications
- Construction
- Engineering
- Foundry work
- General assembly
- Light duty maintenance and repair
- Woodworking

### Use Limitation

- Never modify or alter this product
- Do not use this product against hazards other than those specified in this document.
- In accordance with EN166:2001 safety spectacles cannot be tested and approved for use against liquid droplets. Where liquid protection is specified a suitable product should be considered, for example safety goggles.

## Standards and Approval

This protective eyewear has been shown to meet the basic safety requirements under Article 10 of the European Community Directive 89/686/EEC and is thus CE marked.

These products have been examined at the design stage by INSPEC International Ltd., 56 Leslie Hough Way, Salford, Greater Manchester, M6 6AJ, United Kingdom (Notified Body number 0194).

These products are tested and CE approved against EN166:2001.

## Materials Listing

### 2800/2802/2805

Component	Material
Lens	Polycarbonate
Ratchet holder	Polyamide
Ratchet	Polyamide
Temple slider	Polyamide
Temple tip	Polyamide
Temple screws	Stainless steel
Weight	39g

## Important Notice

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.

## Marking

The products have demonstrated compliance with the requirements of EN 166:2001 and associated standards and bear the following marks:

### Lens marking

Clear lens	2C-1.2 3M 1 FT
Amber lens	2-1.2 3M 1 FT
Weldingshade lens	4-5 3M 1 FT

Note: The Weldingshade lens is marked 4-5 but has also demonstrated compliance with the requirements for welding shade 5.

### Frame marking

Frame 2800	3M 2800 EN166 FT CE
Frame 2802	3M 2802 EN166 FT CE
Frame 2805	3M 2805 EN166 FT CE

## Explanation of Marking

Marking	Description
2-1.2 and 2C-1.2 (EN 170:2002)	UV protection. This product conforms to the requirements of the standard, providing UV protection for the complete specified range (210nm – 365nm). Products marked C provide good colour recognition.
4-5 (EN 171:2002)	Infrared filter providing protection against IR protection for the specified range (780nm to 2000nm).
5 (EN 169:2002)	Welding lens providing protection against UV for the specified range (210nm to 365nm) and IR protection for the specified range (780nm to 2000nm).
1	Optical class
F	Impact protection against high speed particle at low energy (45m/s)
T	Tested for impact protection at extreme temperature conditions -5°C and +55°C



Distributed by Industrial Scientific which is a division of Camlab Ltd

Camlab Ltd, Norman Way Industrial Estate, Over, Cambridge, CB24 5WE  
Telephone: +44 (0)1954 233145  
Email: sales@camlab.co.uk  
www.industrialscientific.co.uk

3M is a trademark of 3M company.  
Please recycle. © 3M 2013.  
All rights reserved.  
18349