



Model:
IM-3

Typology:
INVERTED RESEARCH MICROSCOPE

Description:
Laboratory inverted microscope for research applications. Dye-cast frame, with high stability and ergonomy, for transmitted light observation.

Illumination	Light source type X-LED [®] with white 8W LED; light intensity control using a knob on left side of the frame. Color temperature: 6300K LED average life time approx. 50.000h Voltage: 110/240Vac, 50/60Hz, 1A ; Fuse: T500mA 250V Max power required: 13W
Observation Modes	Brightfield, phase contrast
Focusing	Coaxial coarse and fine focusing mechanism (graduated, 0.002mm) with upper stop, to prevent the contact between objective and specimen. Adjustable tension of coarse focusing knob.
Stage	Fixed stage, dimensions 250x160 mm. 2 stage insert (glass and metal) with hole for small dimension specimens. OPTIONAL: Mechanical stage mountable on the right side of the stage, total dimension=250x230 mm, X-Y translation range 120x80 mm, metallic interchangeable inserts for slides, Petri dishes, Terasaki, multi-Well plates, etc.
Nosepiece	Quintuple revolving nosepiece, rotation on ball bearings.
Head	Trinocular observation head, inclined 45°. Diopter adjustment on left eyepiece. Interpupillary adjustment 50-75 mm.
Eyepieces	Wide field eyepieces WF10X/22 with field number 22.
Objectives	Infinity corrected optical system IOS (Infinity Optical System). Plan-achromatic LWD objectives infinity corrected, for thickness 1.2 mm, made by following objectives: -) Plan-achromatic IOS LWD 10XPh, N.A. 0.25, W.D. 7.94 mm -) Plan-achromatic IOS LWD 20XPh, N.A. 0.40, W.D. 7.66 mm -) Plan-achromatic IOS LWD 40XPh, N.A. 0.60, W.D. 3.71 mm All objectives are treated with an anti-fungus treatment.
Condenser	LWD condenser, N.A. 0.30, working distance 72 mm. The condenser can be removed to extend the working distance up to 150 mm. Precentered slider with phase rings 4X/10X and 20X/40X.
Dimensions	HEIGHT: 495 mm WIDTH: 230 mm WIDTH WITH OPTIONAL MECHANICAL STAGE: 300 mm DEPTH: 540 mm WEIGHT: 9 kg
Accessories	Blue and green filters, instruction manual and dust cover included.