
Basic line - glassware washer 60 cm

GW0160

LABORATORY GLASSWARE WASHER

- washing up to 85°C - antibacterial thermal disinfection
- electronic programming: 7 set programs
- microprocessor electronic control
- active thermodynamic drying
- alkaline powder detergent dispenser
- peristaltic pump for acid liquid neutralizer
- washing chamber and internal door in AISI 304 stainless steel
- external panels made in AISI 304 stainless steel
- 2 independent washing levels through telescopic guides
- external dimensions LxWxH (mm) 600x605x850
- internal working dimensions LxWxH (mm) 520x515x545
- incorporated water softener with salt sensor
- cold water and demineralized water connections
- electronic door lock system for user safety
- electrical connection 3P+N 400V 50Hz 7kW max
- single phase version available 1/N/PE 230V 50Hz 2.8Kw max (GW0160-1)
- 60Hz version available
- without trolleys



Machine optionals

- AS4060 - AQUA STOP WATER LEAK KIT
- B6040L - STAINLESS STEEL PLINTH FOR 60 CM MACHINES WITH LOCK
- IRCP - CEILING SPRAY ARM
- P14060 - PERISTALTIC PUMP FOR LIQUID DETERGENT
- PAD1 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2R - PAD2 RELAY KIT
- T6040 - STAINLESS STEEL FRAME FOR 60 CM MACHINES
- TOP60I - BUILT-IN TOP 60 CM