





MPC 301 Z Superior Chemical Duty Diaphragm Pump

- Dry and oil-free applications
- Outstanding Chemical Resistance
- Maintenance-Free Operation



www.ilmvac.com

MPC 301 Z

The Reliable Classic For Oil - Free Applications

High Quality Chemical Duty Diaphragm Pump

Once more a chemical resistant diaphragm pump shows the perfect adaptation to laboratory needs of oil-free applications. Due to its light weight design and the selection of special PTFE building parts, the MPC 301 Z is chemically resistant against aggressive solvents and acidic vapours that are typically used in laboratory routine. The regulation of the needed vacuum level can be achieved through the wide accessory range of the MPC 301 Z, that way the pump can be adapted to your specific application, e.g. with the use of a vacuum control box or a dial gauge.

High Quality Chemical Duty Diaphragm Pump

The MPC 301 Z can widely be used as a backing pump for rotary evaporators, vacuum ovens or gel dryer. Its easy handling as well as the extreme quiet running of the pump offers its user also to utilize it for vacuum filtration, vacuum concentrating, distillation and desiccation.

Applications:

- Filtration of aquoes, organic, corrosive or acids/bases liquids
- Mobile Phase Filtration/Degassing
- Solid Phase Extraction (SPE)
- Bottle-top Filtration
- Solvent Degassing and Desiccation

Design Features: Analytically pure, oil free vacuum Powerful corrossion resistant diaphragm Light weight, rugged design Manual Vacuum vacuum pump regulator with build-in Allwetted parts are made of dial gauge and Ryton, Viton or Kalrez liquid trap Designed for contious Maintenance-free running drive system and Use in the lab or in the field proven long diaphragm life (with optional adapter) Requires minimal Certification: benchtop space CE Marked due to compact design

Technical Features/Ordering Information :

Model	Pumping Speed I/min	Ultimate Pres- sure mbar	Tubing Needed mm	Dimensions W/D/H mm	Weight kg	CAT. No.
Diaphragm Pump, Chemical Duty, MPC 301 Z, 230V, 50/60 Hz	38	8	DN 8	230/265/169	14.0	412722

Scope of Delivery: Every pump is supplied with ON/OFF switch and internal protective thermal switch for the motor, carry handle and vibration isolating feet. Delivered with Schuko, UK plug leads and operation manual.

Accessories:



Fitting Kit for MP, MPC CAT. No. 404005







Vacuum Regulator w. Dial Gauge CAT. No. 700553

