



Vented Storage Cabinet




Ref : ministore 822A
ministore placed on a work surface.



Ref : ministore 822B
ministore placed on an optional base.



Ref : ministore 822C
ministore mounted to a wall.



Ref : ministore 822D
ministore placed under a work surface.

Dimensions	Width	Depth	Height
mm - inch			
Internal	753 29 2/3"	322 12 2/3"	519 20 2/5"
External	819 32 1/4"	350 14"	725 28 1/2"

Dimensions	Width	Depth	Height
mm - inch			
Internal	753 29 2/3"	322 12 2/3"	519 20 2/5"
External	819 32 1/4"	433 17"	911 35 6/7"

Dimensions	Width	Depth	Height
mm - inch			
Internal	753 29 2/3"	322 12 2/3"	519 20 2/5"
External	819 32 1/4"	350 14"	725 28 1/2"

Dimensions	Width	Depth	Height
mm - inch			
Internal	753 29 2/3"	322 12 2/3"	519 20 2/5"
External	819 32 1/4"	350 14"	725 28 1/2"

Specifications

Volume of air treated	75 m ³ /h
Storage capacity	48 x 1 liter bottles or flasks
Spill tray	2 x 2 liter spill trays with absorbing mats
Structure	galvanized steel with epoxy-polyester anti-acid coating
Total power consumption	20 Watt
Maximum amperage absorbed	0.1 A
Voltage / Frequency	230 Volts / 50 hertz
Blower	Turbine Sound level
Very silent	Very silent only 45 dbA
Weight of the packed unit	822A = 31 kg 822B = 35 kg

Options

- Ref PIDDI011 : Set of 10 absorbing mats
- Ref A1 : Kit to place on a work surface
- Ref B1 : Base
- Ref C1 : Wall base
- Ref D1 : Kit to place under a work surface