

OS40-S & OS20-S Overhead Stirrers



Features


- LED display
- Brushless DC motor
- Variable speed 0-2200rpm
- Overload protection

The Camlab Choice OS40-S and OS20-S overhead stirrers are highly reliable and designed for long term service and durability. Speed rated from 0-2200rpm, and available for 40 or 20 litre maximum stirring capability, the OS40 and OS20 S range have LED displays and overload protection.

They are easy to use and have a range of paddle accessories to choose from.

Specifications

	OS40-S	OS20-S
Part Number	1189958	1189960
Frequency Hz	50/60	50/60
Max stirring qty Litres	40	20
Speed range rpm	0-2200	0-2200
Max Torque Ncm	60	40
Dimensions	83 x 220 x 186	83 x 220 x 186
Weight Kg	2.8	2.6
Power Watts	130	70
Max Viscosity mPas	50000	10000



Accessories

Cat No	Description	Shaft Length [cm]	Stirrer Diameter [cm]	Material
1189964	Blade stirrer	40	6.8	316L stainless steel
1189967	Straight stirrer	35	7.0	PTFE coated
1189962	Crossed stirrer	40	5.0	316L stainless steel
1189965	Centrifugal stirrer	40	9.0	316L stainless steel
1189968	Blade stirrer	35	6.8	PTFE coated
1189963	Straight stirrer	40	6.0	316L stainless steel
1189966	Crossed stirrer	35	6.5	PTFE coated
1189969	Centrifugal stirrer	35	8.5	PTFE coated
1189961	Universal stand & plate	20cm Wide x 31cm Depth x Height 78cm		



1189964



1189967



1189962



1189965



1189968



1189963



1189966



1189969



1189961