

Pocket Colorimeter™ II



Rugged



Portable and convenient



Colorimeter

Each Hach Pocket Colorimeter II measures one to two parameters—many at two concentration ranges. Each instrument comes in a ready-to-use kit that includes a manual, pre-measured unit dose reagents, sample cells, and a sturdy custom carrying case.

DW

WW

PW

IW

E

FB

Features and Benefits

Simple as Ever

Just four buttons on the Hach Pocket Colorimeter II allow easy operation. The Read/Enter key is used when measuring sample concentrations or to confirm menu choices. The Menu key provides quick menu navigation and selection. Use the Zero/Scroll key to zero the instrument or to scroll through menu options. The Power/Backlight key turns the instrument on and toggles the display backlight for low light conditions.

Waterproof, Rugged, and Light Weight

The IP67 rating means the Pocket Colorimeter II will resist the elements and still function properly. A tough, impact-resistant shell protects the electronics and optics. Weighing only 0.2 kg—about a half pound—it even floats! A lanyard keeps the cap attached to the colorimeter.

Large Display and Data Logging

The Range Indicator icon on the display of the colorimeter indicates either the instrument range or the parameter being tested. For many parameters, the instrument can measure in two different ranges. The battery icon will indicate when the batteries need to be replaced. Record the ten most recent data points and the time the measurements were made—no need to record results manually.

Accurate, Reproducible Measurements

The Pocket Colorimeter II offers accuracy and reproducibility comparable to expensive lab instruments, but is designed for a long working life in harsh conditions. A long-lasting LED is used as the light source, and low power requirements assure long battery life.

Pre-programmed

The instruments are factory programmed for one or two of more than 30 parameters. Many are based on EPA-approved methods. No manual calibration is ever required. Simply zero the instrument with a blank, insert the reacted sample, and read the result.

Better Optics

The higher absorbance range provided by the improved quality of the optical system provides expanded ranges for several parameters—reducing the need for dilutions.

DW = drinking water WW = wastewater municipal PW = pure water / power
IW = industrial water E = environmental C = collections FB = food and beverage



Be Right™

Specifications*

Lamp Light Emitting Diode (LED)	Absorbance Range 0 to 2.5 Abs	Compliance European CE mark
Detector Silicon	Sample Cell Pathlength 1 cm and 22 mm	Warranty 2 years
Enclosure IP67, waterproof at 1 m for 30 minutes (battery compartment excluded)	Operating Conditions 0 to 50°C (32 to 122°F) 0 to 90% relative humidity	Dimensions 6.1 x 15.5 x 3.5 cm (2.5 x 6.2 x 1.4 in.)
Wavelength Fixed wavelength ± 2 nm, varies with model	Display LCD, backlit	Weight 0.23 kg (0.5 lbs.)
Filter Bandwidth 15 nm	Power Supply 4 AAA batteries; approximate life of 2000 tests (use of backlight reduces this number)	

*Specifications subject to change without notice.

Parameters

Parameter	Range	Method
Alachlor	0.1, 0.5 ppb thresholds	Immunoassay
Aluminum	0.01 to 0.80 mg/L Al	Aluminon
Ammonia	0.01 to 0.80 mg/L NH ₃ -N	Salicylate
Ammonia, Free and Monochloramine	0.02 to 0.50 mg/L Free Ammonia as NH ₃ -N; 0.04 to 4.50 mg/L Monochloramine as Cl ₂	Indophenol
Atrazine	0.1, 0.5, 3.0 ppb thresholds	Immunoassay
Bromine	0.05 to 4.50; 0.2 to 10 mg/L Br ₂	DPD
Chlorine, Free* and Total* **	0.02 to 2.00; 0.1 to 8.0 mg/L Cl ₂	DPD
Chlorine, Free, Total, and pH[†]	0.1 to 10.0 mg/L Cl ₂ 6.0 to 8.5 pH	DPD Phenol Red
Chlorine, Free* and Total* ** SwifTest Dispenser	0.02 to 2.00; 0.1 to 8.0 mg/L Cl ₂	DPD
Chlorine Dioxide*	0.05 to 5.00 mg/L ClO ₂	DPD/Glycine
Chromium, Hexavalent**	0.01 to 0.70 mg/L Cr ⁶⁺	1,5 Diphenylcarbohydrazide
Copper**	0.04 to 5.00 mg/L Cu	Bicinchoninate
Fluoride* **	0.1 to 2.0 mg/L F ⁻	SPADNS
Iron, FerroVer®**	0.02 to 5.00 mg/L Fe	FerroVer
Iron, TPTZ	0.01 to 1.70 mg/L Fe	TPTZ
Lead, LeadTrak™	5 to 150 µg/L Pb	Fast Column Extraction
Manganese, Low Range	0.01 to 0.70 mg/L Mn	PAN
Manganese, High Range**	0.2-20.0 mg/L Mn	Periodate Oxidation
Molybdate	0.02 to 3.00; 0.1 to 12.0 mg/L Mo	Ternary Complex
Monochloramine and Free Ammonia	0.04 to 4.50 mg/L Monochloramine as Cl ₂ ; 0.02 to 0.50 mg/L Free Ammonia as NH ₃ -N	Indophenol
Nickel and Cobalt	0.01 to 1.00 mg/L Ni; 0.02 to 2.00 mg/L Co	PAN
Nitrate	0.4 to 30.0 mg/L as NO ₃ -N	Cadmium Reduction
Oxygen, Dissolved	0.2 to 10.0 mg/L O ₂	HRDO
Ozone	0.01 to 0.25; 0.01 to 0.75 mg/L O ₃	Indigo Trisulfonate
PCB in Soil	1, 5, 10, 50 ppm thresholds	Immunoassay
Phosphate* **	0.02 to 3.00 mg/L PO ₄	PhosVer® 3
Phosphonate	0.1 to 2.5; 1 to 125 mg/L as PO ₄	PhosVer 3 with UV Digestion

Continued on next page.

Parameters *continued*

Parameter	Range	Method
Silica	1 to 100 mg/L SiO ₂	Silicomolybdate
Sulfate**	2 to 70 mg/L SO ₄	Turbidimetric
TPH in Soil	20, 50, 100, 200 ppm thresholds	Immunoassay
TPH in Water	2, 5, 10, 20 ppm thresholds	Immunoassay
Zinc**	0.02 to 3.00 mg/L Zn	Zincon

*Method is USEPA accepted or approved for drinking water (additional steps may be required)

**Method is USEPA accepted or approved for wastewater (additional steps may be required)

†Phenol Red colorimetric pH measurement is not accepted for regulatory reporting.

‡Greater sensitivity (0.01 mg/L) is achieved by substituting bottled SPADNS reagent for the AccuVac® Ampuls provided in the kit.

Ordering Information

The Hach Pocket Colorimeter II includes manual, pre-measured unit dose reagents, sample cells, and a carrying case. Reagents can be refilled by contacting Hach or your Hach distributor.

2812900	Alachlor Pocket Colorimeter II; includes reagents for 18 tests	5870021	Lead, LeadTrak Pocket Colorimeter II; includes reagents for 20 tests
5870025	Aluminum Pocket Colorimeter II; includes reagents for 100 tests	5870018	Manganese, Low Range, Pocket Colorimeter II; includes reagents for 50 tests
5870040	Ammonia Pocket Colorimeter II; includes reagents for 100 tests	5870015	Manganese, High Range, Pocket Colorimeter II; includes reagents for 100 tests
5870026	Ammonia, Free and Monochloramine Pocket Colorimeter II; includes reagents for 50 tests Free Ammonia, 100 tests Monochloramine	5870010	Molybdate Pocket Colorimeter II; includes reagents for 100 tests
2763500	Atrazine Pocket Colorimeter II; includes reagents for 18 tests	5870020	Nickel and Cobalt Pocket Colorimeter II; includes reagents for 100 tests
5870001	Bromine Pocket Colorimeter II; includes reagents for 50 to 100 tests	5870002	Nitrate Pocket Colorimeter II; includes reagents for 100 tests
5870000	Chlorine, Free and Total Pocket Colorimeter II; includes reagents for 50 to 100 tests	5870003	Oxygen, Dissolved Pocket Colorimeter II; includes reagents for 50 tests
5870012	Chlorine, Free, Total, and pH Pocket Colorimeter II; includes reagents for 100 tests	5870004	Ozone Pocket Colorimeter II; includes reagents for up to 50 tests
5870023	Chlorine, Free, SwifTest Dispenser Pocket Colorimeter II; includes reagents for 125 to 250 tests	2773400	PCB in Soil Pocket Colorimeter II; includes reagents for 18 tests
5870024	Chlorine, Total SwifTest Dispenser Pocket Colorimeter II; includes reagents for 125 to 250 tests	5870006	Phosphate Pocket Colorimeter II; includes reagents for 100 tests
5870051	Chlorine Dioxide Pocket Colorimeter II; includes reagents for 100 tests	5870007	Phosphonate Pocket Colorimeter II; includes reagents for 100 tests
5870017	Chromium, Hexavalent Pocket Colorimeter II; includes reagents for 100 tests	5870034	Silica Pocket Colorimeter II; includes reagents for 100 tests
5870019	Copper Pocket Colorimeter II; includes reagents for 100 tests	5870029	Sulfate Pocket Colorimeter II; includes reagents for 100 tests
5870005	Fluoride Pocket Colorimeter II; includes reagents for up to 50 tests	2775000	TPH in Soil Pocket Colorimeter II; includes reagents for 18 tests
5870022	Iron, FerroVer Pocket Colorimeter II; includes reagents for 100 tests	2774200	TPH in Water Pocket Colorimeter II; includes reagents for 18 tests
5870016	Iron, TPTZ Pocket Colorimeter II; includes reagents for 100 tests	5870009	Zinc Pocket Colorimeter II; includes reagents for 100 tests

Continued on next page.

Ordering Information *continued*

Wavelength-specific Pocket Colorimeters

Program custom methods and calibrations on two channels.

- 5870042** Pocket Colorimeter II; Light Wavelength 420 nm
- 5870045** Pocket Colorimeter II; Light Wavelength 450 nm
- 5870050** Pocket Colorimeter II; Light Wavelength 500 nm
- 5870052** Pocket Colorimeter II; Light Wavelength 528 nm
- 5870055** Pocket Colorimeter II; Light Wavelength 550 nm
- 5870058** Pocket Colorimeter II; Light Wavelength 580 nm
- 5870060** Pocket Colorimeter II; Light Wavelength 600 nm
- 5870065** Pocket Colorimeter II; Light Wavelength 655 nm

Standards

Spec \checkmark Ampule Standards are colored gels that simulate the color produced by the analytical procedure, for simple checks on instrument response. Each set includes a blank and three concentrations.

- 2635300** Chlorine Spec \checkmark Standard Kit, DPD LR (0 to 2.0 mg/L Cl₂); set of 4 vials
- 2893300** Chlorine Spec \checkmark Standard Kit, DPD HR (0 to 6.5 mg/L Cl₂); set of 4 vials
- 2712500** Fluoride Spec \checkmark Standard Kit (0 to 2.00 mg/L F⁻); set of 4 vials
- 2507500** Monochloramine/Free Ammonia Spec \checkmark Standard Kit (0 to 4.5 mg/L Cl₂ and 0 to 0.50 mg/L NH₃-N); set of 4 vials
- 2708000** Ozone MR Spec \checkmark Standard Kit (0 to 0.75 mg/L); set of 4 vials

Accessory

- 5953100** Pocket Colorimeter II Soft-Sided Case/Holster (holds colorimeter, two sample cells and reagent pouches)



The optional soft-sided case/holster holds the Pocket Colorimeter, two vials, and more!

Lit. No. 2596

173 Printed in U.S.A.

©Hach Company, 2007. All rights reserved.

In the interest of improving and updating its equipment, Hach Company reserves the right to alter specifications to equipment at any time.

At Hach, it's about learning from our customers and providing the right answers. It's more than ensuring the quality of water—it's about ensuring the quality of life. When it comes to the things that touch our lives...

Keep it pure.

Make it simple.

Be right.

For current price information, technical support, and ordering assistance, contact the Hach office or distributor serving your area.

In the United States, contact:

HACH COMPANY World Headquarters
P.O. Box 389
Loveland, Colorado 80539-0389
U.S.A.
Telephone: 800-227-4224
Fax: 970-669-2932
E-mail: orders@hach.com
www.hach.com

U.S. exporters and customers in Canada, Latin America, sub-Saharan Africa, Asia, and Australia/New Zealand, contact:

HACH COMPANY World Headquarters
P.O. Box 389
Loveland, Colorado 80539-0389
U.S.A.
Telephone: 970-669-3050
Fax: 970-461-3939
E-mail: intl@hach.com
www.hach.com

In Europe, the Middle East, and Mediterranean Africa, contact:

HACH LANGE GmbH
Willstätterstraße 11
D-40549 Düsseldorf
GERMANY
Tel: +49 (0) 211 5288-0
Fax: +49 (0) 211 5288-143
E-mail: info@hach-lange.de
www.hach-lange.com



Be Right™