Classic Portable Autoclave







Prestige Medical Classic – with more than 1 million sold in 80 countries worldwide, you can rely on our reputation for quality and performance.

Technical Specification

| Model Number | 210001 | 210002 | 210004 | 210006 | 210007 | 210008 | 210011 | 210047 | 210048 | 210134 |
|-------------------------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| Max width - overall | 340mm | 340mn |
| Max height - overall | 335mm | 420mm | 420mm | 335mm | 420mm | 335mm | 335mm | 335mm | 420mm | 335mn |
| Max net weight | 4.0kg | 4.8kg | 4.8kg | 5.3kg | 4.8kg | 4.0kg | 4.0kg | 4.0kg | 4.8kg | 5.4kç |
| Chamber diameter | 210mm |
| Chamber height | 236mm | 328mm | 328mm | 236mm | 328mm | 236mm | 236mm | 236mm | 328mm | 236mm |
| Chamber capacity | 9 litres | 12 litres | 12 litres | 9 litres | 12 litres | 9 litres | 9 litres | 9 litres | 12 litres | 9 litres |
| Max instrument length | 228mm | 290mm | 290mm | 228mm | 290mm | 228mm | 228mm | 228mm | 290mm | 228mm |
| Max load weight | 3kg | 4kg | 4kg | 3kg | 4kg | 3kg | 3kg | 3kg | 4kg | 3kg |
| Sterilizing temperature | 126°C | 126°C | 126°C | 121°C | 121°C | 121°C | 126°C | 121°C | 121°C | 134°C |
| Min sterilizing time | 11 minutes | 11 minutes | 11 minutes | 18 minutes | 18 minutes | 16 minutes | 11 minutes | 22 minutes | 22 minutes | 3 minutes |
| Cycle time - normal | 22 minutes | 22 minutes | 22 minutes | 28 minutes | 30 minutes | 26 minutes | 22 minutes | 70 minutes | 70 minutes | 20 minutes |
| Operating pressure | 1.4 bar | 1.4 bar | 1.4 bar | 1.05 bar | 1.05 bar | 1.05 bar | 1.4 bar | 1.05 bar | 1.05 bar | 2.2 baı |
| Voltage | 230v | 230v | 230v | 110v | 110v | 230v | 230v | 230v | 230v | 230\ |
| Wattage | 1500w | 1500w | 1500w | 1200w | 1200w | 1500w | 1500w | 1500w | 1500w | 1500w |
| Frequency | 50-60Hz |
| Temperature & Pressure Gauges | | | 1 | | | | | | | 1 |
| Furniture | 219708 | 219720 | 219720 | 219708 | 219720 | 219708 | 219708 | 219708 | 219720 | 219708 |
| | | | | | | | 219706 | | | |
| | | | | | | | 219294 | | | |







A wide choice of accessories - allows you to specify the model to suit your exact needs.



Reliable and trusted worldwide

Designed to give you the most cost effective sterilization solution with a wide choice of models and accessories that are guaranteed to meet your needs.

Steam sterilization, or autoclaving, is the preferred method of eliminating the risk of cross infection through contaminated instruments. It is the only method recommended throughout the world by healthcare professionals including the World Health Organisation (WHO) and the Centre for Disease Control (CDC).



Prestige Medical - integrated decontamination solutions

Prestige Medical Ltd is an ISO 9001-2000/EN13485 quality accredited company. The Classic is designed to the latest international standards for safety and performance and is fully CE marked to the Medical Devices Directive 93/42/EEC. Manufactured in the UK, the Classic complies either fully or in part with the following standards:

standards and guidelines

Designed and manufactured to comply with the following standards and guidelines:

EN61010-1:1995 Electrical safety

IEC 601 Electrical and product safety standards
DIN 58946 Part 8 Type testing for microbiological performance

EMC Electro Magnetic EN 50081-1, EN 50082-1 and

Compatibility EN 50082-2 are generic standards relating to EMC BS 3970 Part 4 British Standards for Autoclaves. Pressure vessel

complies.

ESCHLE Electrical Safety Code for Hospital Laboratory

Equipment (UK)

UL 544 Underwriters Laboratory (America) covering electrical

and product safety.

CSA Std C22.2 Canadian Standards Association covering electrical

and product safety.

FDA 510k
Food and Drug Administration (America)

guarantee

- Pressure chamber and heating element 10 years
- 12 months warranty on parts







24 Norman Way Industrial Estate, Over, Cambridge, CB24 5WE

Tel: +44(0)1954 233 100 Fax: +44(0)1954 233 101 Email: sales@camlab.co.uk Web: www.camlab.co.uk