

GW4060S

€ 6.020,00

LABORATORY GLASSWARE WASHER WITH DRYING SYSTEM

- washing up to 95°C - antibacterial thermal disinfection
- electronic programming: 9 set programs + 6 free programs
- microprocessor programmable electronic control
- serial port RS232 for connection to external printer or PC
- forced hot air drying system with air filter 98% DOP
- peristaltic pump for liquid detergent
- peristaltic pump for acid liquid neutralizer
- possibility of installing one additional peristaltic pump
- washing chamber and internal door in AISI 316L stainless steel
- external panels made in AISI 304 stainless steel
- 2 independent washing levels through telescopic guides
- external dimensions LxWxH (mm) 600x605x850
- internal working dimensions LxWxH (mm) 520x515x545
- incorporated water softener with salt sensor
- cold water and demineralized water connections
- electronic door lock system for user safety
- electrical connection 3P+N 400V 50Hz 7kW max
- single phase version available 1/N/PE 230V 50Hz 2.8Kw max (GW4060S1)
- 60Hz version available
- without trolleys



Machine optionals

- AF4060 - ABSOLUTE HEPA FILTER
- AS4060 - AQUA STOP WATER LEAK KIT
- B6040L - STAINLESS STEEL PLINTH FOR 60 CM MACHINES WITH LOCK
- FLUX4060 - DETERGENT DOSAGE CONTROL FOR ADDITIONALS PERISTALTIC PUMPS
- IRCP - CEILING SPRAY ARM
- P34060 - PERISTALTIC PUMP FOR LIQUID ADDITIVES
- PAD1 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2 - BOOSTER PUMP FOR NON-PRESSURE DEMINERALIZED WATER
- PAD2R - PAD2 RELAY KIT
- T6040 - STAINLESS STEEL FRAME FOR 60 CM MACHINES
- TOP60I - BUILT-IN TOP 60 CM
- WD-LANE - DATA COMMUNICATION CARD
- WD-LS3060 - DETERGENT LEVEL SENSOR
- WD-PRINTE - EXTERNAL PRINTER