

## THE VARIOUS WORKTOPS

WORKTOP	COMPOSITION	DIMENSIONS	TECHNICAL SPECIFICATIONS	USES
<u>POSTFORMED LAMINATE</u>	Several layers of kraft paper impregnated of phenolic resin	Length : 600, 900, 1200, 1500, or 1800. Depth : 600 ou 750. Thickness : 28 mm.	Heat resistance at 180° Resistance to common household products Good resistance to light Shocks resistance	Physics, electronics, material testing and school laboratories For non-corrosive products
<u>ENAMELLED GLASS</u>	Tempered glass bonded in factory on a waterproof chipboard (unleaded)	Length : 600, 900, 1200, 1500, or 1800. Depth : 600 ou 750. Thickness : 6 mm + Waterproof support : 22 mm.	Resistance to mechanical shocks Resistance to flexion Resistance to heat constraints	For all type of laboratories particularly where there are problems of cleaning and decontamination
<u>CERAMIC TILE ON WATERPROOF SUPPORT</u>	Material with the characteristics of glazed stoneware and the flatness of the enamelled glass. Glued and jointed in factory on a waterproof chipboard.	Length : 600, 900, 1200, 1500, or 1800. Depth : 600 ou 750. Thickness : 8 mm + Waterproof support : 22 mm.	Non-porous surface so working conditions where hygiene is perfect Resistance to flexion Resistance to pressure Resistance to UV Resistance to acids and chemicals except hydrofluoric acid	Chemistry, physics and biology laboratories Use of corrosive products Sciences, medical, pharmaceutical and food-processing laboratories
<u>COMPACT RESIN ON WATERPROOF SUPPORT</u>	Decorative high pressure laminate consisting of layers of kraft impregnated of phenolic resin and 2 decorative films impregnated of aminoplast resin on the external faces	Length : 600, 900, 1200, 1500, or 1800. Depth : 600 ou 750. Thickness : 8 mm + Waterproof support : 22 mm.	Excellent mechanical resistance like shocks, flexion, tensile and heat Average moisture resistance	Like laminate but with better resistance to humidity
<u>TRESPA ATHLON</u>	synthetic resin with high resistance reinforced evenly by wood fibers	Length : 600, 900, 1200, 1500, or 1800. Depth : 600 ou 750. Thickness : 8 mm + Waterproof support : 22 mm.	Excellent resistance to vapor, abrasion and humidity Resistance to chemicals Great resistance to shocks Excellent behaviour to fire	Like enamelled glass : For all type of laboratories particularly where there are problems of cleaning and decontamination And more : Physics and electronics laboratories