

Characteristics Labster ESD stool



Article:	9107E - artificial leather	
Dimensions in mm	Seat:	H 450-650 B 380 T 380
	Weight:	6,0 kg
	Volume:	0,04 m ³



Distributed and Supported in the UK by:



24 Norman Way Industrial Estate, Over, Cambridge, CB24 5WE
Tel: +44(0)1954 233 100 Fax: +44(0)1954 233 101
Email: sales@camlab.co.uk Web: www.camlab.co.uk

Base equipment

Benefit

Hygienic quality	Consistent hygienic design. Quasi seamless, no nooks and crannies, soft cover on ring release. Completely washable and resistant to desinfectant	Cleaning / decontamination is quick, easy, thorough and safe.
Laboratory qualification	GMP-compatible and suitable for use in clean rooms. Can be used in laboratories of safety class S1 to S3.	Suitable for laboratory and hygiene-critical areas of all types and in particular for use in the health sector, biotechnology and pharmaceuticals.
Conductivity	The metal components have a conductive coating All plastic parts are also conductive Typical discharge resistance of 10 ⁶ Ω Conductive glides	Exceeds the requirements of ESD protection according to standard DIN EN 61340-5-1 100% ESD protection
Seat	Extra large seat with a diameter of 380 mm.	The extra-strong comfort upholstery offers excellent seating comfort.
Seat design	Conductive synthetic leather cushion with seamless upholstery technique and high quality Skai synthetic leather. Washable and resistant to disinfectant. Available in the color black (2571).	The extra-strong comfort upholstery offers excellent seating comfort. Soft and comfortable upholstery provides a comfortable feel Resistant to disinfectants, washable and easy-care Ideal for the use in laboratories
Seat height	Infinitely variable seat height adjustment from 450-650 mm through self-supporting safety pneumatic spring	Large seat height adjustment range.
Technology	Ring release	The height can be adjusted at any handle position around the stool.
Base	Compact, round flat base	Can be stowed away under desks to save space. The round base prevents it getting caught anywhere.
Castors/Glides	Load-dependent, braked double-castors for hard floors.	Chair does not roll away when not in use, thus minimised accident risk.
Material used	All materials are pure and recycable.	Environmentally friendly
Standards	DIN EN European standard 61340-5-1 for ESD-protected areas DIN EN ISO 14644-1 Air purity class 3 GMP - compatible Laboratory safety class S1 to S3 GS symbol for „Tested safety“ Quality management system DIN EN ISO 9001 EEC Directive No. 1836/93 and Environmental management system DIN EN ISO 14001	100% ESD protection Certified laboratory suitability Tested by Fraunhofer Institut IAO Safeguarded procurement.
Warranty	5 year long-term warranty of which 3 year full warranty	Guaranteed quality and high efficiency