

DURAN® RANGE OF BURETTES



Product Range	DURAN®BURETTES				
Accuracy class	Class AS				Class B
Material of the burettes: DURAN®glass					
Certificate*	Batch certificate	Batch certificate	Batch certificate	Batch certificate	–
Maximum recommended temperature without affecting accuracy (at 20 °C)	250 °C	250 °C	250 °C	250 °C	250 °C
Glass color	clear glass	amber glass	clear glass	amber glass	clear glass
Print color	Blue	White	Blue	White	Blue
Schellbach stripe	yes	no	yes	no	no
ml	Straight glass stopcock	Straight glass stopcock	Straight PTFE stopcock	Straight PTFE stopcock	Straight glass stopcock
10	24 329 27 04	24 326 27 01	24 330 27 02	24 336 27 08	24 328 27 03
25	24 329 33 06	24 326 33 03	24 330 33 04	24 336 33 01	24 328 33 05
50	24 329 36 06	24 326 36 03	24 330 36 04	24 336 36 01	24 328 36 05
100	24 329 39 06	24 326 39 03	24 330 39 04	24 336 39 01	24 328 39 05

* Batch certificates also available online at www.DWK-LifeScience.com

DURAN® RANGE OF BURETTES



Product Range	DURAN®BURETTES			
	AUTOMATIC BURETTES – PELLET TYPE		MICRO-BURETTES	
Accuracy class	Class AS			
Material of the burettes: DURAN®glass				
Certificate*	Batch certificate	Batch certificate	Batch certificate	Batch certificate
Maximum recommended temperature without affecting accuracy (at 20 °C)	250 °C	250 °C	250 °C	250 °C
Print color	Blue	Blue	Blue	Blue
Schellbach stripe	yes	yes	yes	yes
ml	Lateral glass stopcock	PTFE spindle stopcock, intermediate PTFE stopcock	Straight glass stopcock	Straight PTFE stopcock, intermediate PTFE stopcock
1	–	–	24 320 11 08	24 321 11 09
2	–	–	24 320 16 05	24 321 16 06
5	–	–	24 320 22 07	24 321 22 08
10	24 318 27 54	24 317 27 53	–	24 321 27 05
25	24 318 33 56	24 317 33 55	–	–
50	24 318 36 56	24 317 36 55	–	–

Distributed By: Camlab Ltd
Unit 24, Norman Way Industrial Estate
Over, Cambridge, CB24 5WE, United Kingdom
T: +44 (0) 1954 233 110 E: sales@camlab.co.uk

