


TOP  
S  
P  
O



**HANDZENTRIFUGE**  
Manual Centrifuge

# HANDZENTRIFUGE



## Maintenance-free, bench-mounted manually operated centrifuge

This convenient centrifuge can be easily clamped to a bench or table, and operated without electricity. Its self-lubricating gear makes it virtually maintenance-free.

It can be operated with two different rotors.

With rotor **1014** conical 15 ml tubes (Cat. No. 0515, non-graduated or No. 0516, graduated) can be accelerated to 1,300 RCF.

Rotor **1025** also accommodates a variety of other commercial tubes (also with round bottom) up to 15 ml. The tubes may have a max. length of 125 mm and a max. diameter of 17 mm.



illustrated with rotor 1014  
↘90°

illustrated with rotor 1025  
↘50°

ROTORS	4-place	4-place
Max. capacity	4 x 15 ml <sup>*)</sup>	4 x 15 ml
Max. RPM (speed)	3,000 min <sup>-1</sup>	3,000 min <sup>-1</sup>
Max. RCF	1,300	1,076
<b>Cat. No.</b>	<b>1014</b>	<b>1025</b>

<sup>\*)</sup> conical only

HANDZENTRIFUGE	
<b>Manual centrifuge, without rotor</b>	
Dimensions (HxWxD)	285 x 140 x 175 mm
Weight	approx. 0.9 kg
<b>Cat. No.</b>	<b>1011</b>

Distributed and Supported in the Uk by:



24 Norman Way Industrial Estate, Over, Cambridge, CB24 5WE  
 Tel: +44(0)1954 233 100 Fax: +44(0)1954 233 101  
 Email: sales@camlab.co.uk Web: www.camlab.co.uk

