

# Lovibond® Water Testing Tintometer® Group



## Scuba II

Test equipment for the responsible private swimming pool and whirlpool operator



- Modern, ergonomic design
- User friendly handling
- Watertight housing\*
- Large display

Part Number: 216100-17

### Main pool parameters

Whoever as a private pool owner value accurate measurement results of the important pool parameters, such as Chlorine or pH sets, gets with the Scuba II an ideal test device to the hand. The device works intuitively and measures the most important pool parameters of free chlorine, total chlorine, bromine, pH, alkalinity-m and cyanuric acid.

### Waterproof

And if the device falls into the water? No problem - the Scuba II is not only waterproof but also buoyant.

### Integrated measuring chamber

Take a sample by immersing the measuring chamber in the instrument.

### Fast results

Add a reagent and press "Test" button. The result is available within a few seconds. Or in other words: measuring like the pros.

**Distributed By: Camlab Ltd**  
Unit 24, Norman Way Industrial Estate  
Over, Cambridge, CB24 5WE, United Kingdom  
T: +44 (0) 1954 233 110 E: sales@camlab.co.uk



### Industry

Pool Domestic | Pool Services

### Application

Drinking Water Treatment | Pool Water Control | Pool Water Treatment | Raw Water Treatment | Waste Water Treatment

### Scuba II

Floatable, waterproof and certainly a useful little helper for the pool: The Scuba II is for private pool owners the ideal companion for the bathing season. Measure the most important parameters and hold the results in your hands immediately.

[Convince yourself - here's the Scuba II video](#)

### Measuring Range

Test Name	Measuring Range	Chemical Method
Alkalinity-m T	0 - 300 mg/l CaCO <sub>3</sub>	Acid / Indicator
Bromine T	0.2 - 13 mg/l Br <sub>2</sub>	DPD
Chlorine T	0.1 - 6.0 mg/l Cl <sub>2</sub> <sup>a)</sup>	DPD
CyA T	1 - 160 mg/l CyA	Melamine
pH-value T	6.5 - 8.4	Phenol Red

## Technical Data

<b>Optics</b>	temperature-compensated LED ( $\lambda = 530 \text{ nm}$ ) and photo-sensor
<b>Operation</b>	Foil keypad
<b>Power Supply</b>	2 AAA batteries
<b>Auto – OFF</b>	Yes
<b>Portability</b>	Portable
<b>Environmental Conditions</b>	temperature: 5 – 40 °C relative humidity: 30 – 90 %, non-condensing
<b>Compliance</b>	CE
<b>Dimensions</b>	70 x 45 x 145 mm
<b>Weight</b>	165 g

## Accessories

Title	Part Number
Battery lid for Scuba II	19801802-3
Rubber seal cap for Scuba II	19802218
Stirring rod, blue, 10 cm	364107
ValidCheck Chlorine 1,5 mg/l	48105510

## Delivery Scope

- Scuba II In plastic box
- 20 DPD No.1 tablet reagents
- 20 Phenol Red Photometer tablet reagents
- 10 DPD No.3 tablet reagents
- 10 CyA-Test tablet reagents
- 10 Alka-M-Photometer tablet reagents
- Instruction manual
- 2 Batteries (AAA)
- Stirring rod

### Tintometer GmbH

Lovibond® Water Testing  
Schleefstraße 8-12  
44287 Dortmund  
Tel.: +49 (0)231/94510-0  
Fax: +49 (0)231/94510-30  
sales@lovibond.com  
www.lovibond.com  
Germany

### Tintometer China

Room 1001, China Life Tower  
16 Chaoyangmenwai Avenue,  
Beijing, 100020  
Tel.: +86 10 85251111 App. 330  
Fax: +86 10 85251001  
chinaoffice@tintometer.com  
www.lovibond.com  
China

### Tintometer Inc.

6456 Parkland Drive  
Sarasota, FL 34243  
Tel: 941.756.6410  
Fax: 941.727.9654  
sales@lovibond.us  
www.lovibond.com  
USA

### The Tintometer Limited

Lovibond House  
Sun Rise Way  
Amesbury, SP4 7GR  
Tel.: +44 (0)1980 664800  
Fax: +44 (0)1980 625412  
sales@lovibond.uk  
www.lovibond.com  
UK

### Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,  
Lebu Nilam 2, Bandar Bukit Tinggi,  
Klang, 41200, Selangor D.E  
Tel.: +60 (0)3 3325 2285/6  
Fax: +60 (0)3 3325 2287  
lovibond.asia@tintometer.com  
www.lovibond.com  
Malaysia

### Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
Sanathnagar Industrial Estate,  
Hyderabad, 500018  
Telangana  
Tel: +91 (0) 40 23883300  
Toll Free: 1 800 599 3891/ 3892  
indiaoffice@tintometer.com  
www.lovibondwater.in  
India

### Tintometer AG

Hauptstraße 2  
5212 Hausen AG  
Tel.: +41 (0)56/4422829  
Fax: +41 (0)56/4424121  
info@tintometer.ch  
www.tintometer.ch  
Switzerland

### Tintometer Brazil

Caixa Postal: 271  
CEP: 13201-970  
Jundiaí – SP  
Tel.: +55 (11) 3230-6410  
sales@tintometer.com.br  
www.lovibond.com.br  
Brazil

### Tintometer Spain

Postbox: 24047  
08080 Barcelona  
Tel.: +34 661 606 770  
sales@tintometer.es  
www.lovibond.com  
Spain