

## Material Safety Data Sheet

Date Printed: 20/FEB/2008

Date Updated: 09/FEB/2006

Version 1.11

Regulation (EC) No 1907/2006

---

1 - Product and Company Information

---

Product Name HYDRANAL-COULOMAT CG, REAGENT FOR  
COULO- METRIC KF TITRATION, CATHOLYTE

Product Number 34840

Company Sigma-Aldrich Company Ltd.  
The Old Brickyard  
New Road, Gillingham SP8 4XT  
United Kingdom

Technical Phone # 44-(0)-1747-833000  
Fax 44-(0)-1747-833313  
E-mail Address eurtechserv@sial.com  
Emergency Phone # 44-(0)-1747-833100

---

2 - Hazards Identification

---

## SPECIAL INDICATION OF HAZARDS TO HUMANS AND THE ENVIRONMENT

Highly flammable. Toxic by inhalation, in contact with skin and if swallowed. Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

---

3 - Composition/Information on Ingredients

---

Product Name		CAS #	EC no	Annex I Index Number
HYDRANAL COLOUMAT CG		None	None	None
Ingredient Name	Percent	CAS #	EC no	Annex I Index Number
DIETHANOLAMINE HYDROCHLORIDE	>= 50 <= 60	14426-21-2	238-396-4	None
METHANOL	>= 30 <= 60	67-56-1	200-659-6	603-001-00-X

Symbols: F-T

R-Phrases: 11-23/24/25-39/23/24/25

Highly flammable. Toxic by inhalation, in contact with skin and if swallowed. Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

---

4 - First Aid Measures

---

## AFTER INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen.

## AFTER SKIN CONTACT

In case of skin contact, flush with copious amounts of water for at least 15 minutes. Remove contaminated clothing and shoes. Call a physician.

#### AFTER EYE CONTACT

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

#### AFTER INGESTION

If swallowed, wash out mouth with water provided person is conscious. Call a physician immediately.

---

### 5 - Fire Fighting Measures

---

#### EXTINGUISHING MEDIA

Suitable: Water spray. Carbon dioxide, dry chemical powder, or appropriate foam.

#### SPECIAL RISKS

Specific Hazard(s): Emits toxic fumes under fire conditions. Flammable liquid. Vapor may travel considerable distance to source of ignition and flash back.  
Explosion Hazards: Container explosion may occur under fire conditions. Forms explosive mixtures in air.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS

Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

---

### 6 - Accidental Release Measures

---

#### PERSONAL PRECAUTION PROCEDURES TO BE FOLLOWED IN CASE OF LEAK OR SPILL

Evacuate area. Shut off all sources of ignition.

#### PROCEDURE(S) OF PERSONAL PRECAUTION(S)

Wear self-contained breathing apparatus, rubber boots, and heavy rubber gloves.

#### ENVIRONMENTAL PRECAUTION(S)

Do not allow material to enter drains or water courses. Avoid contaminating sewers and waterways with this material.

#### METHODS FOR CLEANING UP

Cover with dry-lime, sand, or soda ash. Place in covered containers using non-sparking tools and transport outdoors. Ventilate area and wash spill site after material pickup is complete.

---

### 7 - Handling and Storage

---

#### HANDLING

Directions for Safe Handling: Do not breathe vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated exposure. Do not use if skin is cut or scratched. Wash thoroughly after handling.

#### STORAGE

Conditions of Storage: Keep tightly closed. Keep away from heat, sparks, and open flame.

---

### 8 - Exposure Controls / Personal Protection

---

#### ENGINEERING CONTROLS

Safety shower and eye bath. Use nonsparking tools. Use only in a chemical fume hood.

GENERAL HYGIENE MEASURES

Wash thoroughly after handling. Discard contaminated clothing and shoes.

EXPOSURE LIMITS

Country	Source	Type	Value
Poland		NDS	100 MG/M3
Poland		NDSCh	300 MG/M3
Poland		NDSP	-

EXPOSURE LIMITS - DENMARK

Source	Type	Value
OEL	TWA	260 mg/m3
		200 ppm

Remarks: H, methanol

EXPOSURE LIMITS - GERMANY

Source	Type	Value
TRGS 900	OEL	260 mg/m3
		200 ppm

Remarks: 4

Remarks: H, methanol

EXPOSURE LIMITS - NORWAY

Source	Type	Value
OEL	TWA	130 mg/m3
		100 ppm

Remarks: H, methanol

EXPOSURE LIMITS - SWEDEN

Source	Type	Value
	LLV (Level)	250 mg/m3
		200 ppm

Remarks: H

Remarks: methanol

EXPOSURE LIMITS - SWITZERLAND

Source	Type	Value
OEL	OEL	260 mg/m3
		200 ppm

Remarks: H M C

Remarks: methanol

EXPOSURE LIMITS - UNITED KINGDOM

Source	Type	Value
OEL	OEL	266 mg/m3
		200 ppm

Remarks: methanol

OEL	STEL	333 mg/m3
		250 ppm

Remarks: Skin Indicative limit value

Remarks: methanol

PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection: Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Use supplied-air or SCBA respirators. Europe permits the use of type AXBEK full-face cartridge respirators (EN 14387).  
Hand Protection: Compatible chemical-resistant gloves.  
Eye Protection: Chemical safety goggles.

## 9 - Physical and Chemical Properties

---

Appearance	Physical State: Liquid	
Property	Value	At Temperature or Pressure
pH	4.0 - 7.0	20 °C
BP/BP Range	63 °C	
MP/MP Range	N/A	
Flash Point	14 °C	Method: closed cup
Flammability	N/A	
Autoignition Temp	N/A	
Oxidizing Properties	N/A	
Explosive Properties	N/A	
Explosion Limits	N/A	
Vapor Pressure	N/A	
SG/Density	1.064 g/cm <sup>3</sup>	
Partition Coefficient	N/A	
Viscosity	N/A	
Vapor Density	N/A	
Saturated Vapor Conc.	N/A	
Evaporation Rate	N/A	
Bulk Density	N/A	
Decomposition Temp.	N/A	
Solvent Content	N/A	
Water Content	N/A	
Surface Tension	N/A	
Conductivity	N/A	
Miscellaneous Data	N/A	
Solubility	N/A	

---

## 10 - Stability and Reactivity

---

### STABILITY

Stable: Stable.

Materials to Avoid: Acids, Acid chlorides, Acid anhydrides, Oxidizing agents, Alkali metals, Reducing agents.

### HAZARDOUS DECOMPOSITION PRODUCTS

Hazardous Decomposition Products: Carbon monoxide, Carbon dioxide, Nitrogen oxides, Hydrogen iodide, Hydrogen chloride gas, Sulfur oxides.

### HAZARDOUS POLYMERIZATION

Hazardous Polymerization: Will not occur

---

## 11 - Toxicological Information

---

### SIGNS AND SYMPTOMS OF EXPOSURE

Nausea, headache, and vomiting. Gastrointestinal disturbances. Dizziness. Weakness. Confusion. Drowsiness. Unconsciousness. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Ingestion can cause: Methyl alcohol may be fatal or cause blindness if swallowed. Cannot be made non-poisonous.

### ROUTE OF EXPOSURE

Skin Contact: Causes skin irritation.  
Skin Absorption: Toxic if absorbed through skin.  
Eye Contact: Causes eye irritation.  
Inhalation: Material is irritating to mucous membranes and upper respiratory tract. Toxic if inhaled.

Ingestion: Toxic if swallowed.

TARGET ORGAN INFORMATION

Eyes. Kidneys. Liver. Heart.

---

12 - Ecological Information

---

No data available.

---

13 - Disposal Considerations

---

SUBSTANCE DISPOSAL

Contact a licensed professional waste disposal service to dispose of this material. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

---

14 - Transport Information

---

RID/ADR

UN#: 1230  
Class: 3  
PG: II  
Subrisk: 6.1  
Proper Shipping Name: Methanol solution

IMDG

UN#: 1230  
Class: 3  
PG: II  
Subrisk: 6.1  
Proper Shipping Name: Methanol solution  
Marine Pollutant: No  
Severe Marine Pollutant: No

IATA

UN#: 1230  
Class: 3  
PG: II  
Subrisk: 6.1  
Proper Shipping Name: Methanol solution  
Inhalation Packing Group I: No

---

15 - Regulatory Information

---

CLASSIFICATION AND LABELING ACCORDING TO EU DIRECTIVES

INDICATION OF DANGER: F-T

Highly Flammable. Toxic.

R-PHRASES: 11-23/24/25-39/23/24/25

Highly flammable. Toxic by inhalation, in contact with skin and if swallowed. Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

S-PHRASES: 16-36/37-45

Keep away from sources of ignition - no smoking. Wear suitable protective clothing and gloves. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

COUNTRY SPECIFIC INFORMATION

Germany

WGK: 1

Self-Classification

---

16 - Other Information

---

WARRANTY

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Inc., shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. Copyright 2008 Sigma-Aldrich Co. License granted to make unlimited paper copies for internal use only.

DISCLAIMER

For R&D use only. Not for drug, household or other uses.