

1. Identification


Product Code **1110314**

Product Name **ACETIC ANHYDRIDE pure**

Molecular Formula **(CH₃CO)₂O =102.09**

CAS Number **108-24-7**

Supplier: **CAMLAB LIMITED**
Norman Way Industrial Estate
Over
Cambridge
England
CB4 5WE



Phone **01954 233110**


Fax **01954 233101**

Emergency Telephone **08:00-17:00 01954 233110**
24hr 112
(Have this document to hand)

2. Composition

Component	CAS No	EEC No	Conc w/w	Classification & Risk Phrases	Exp (See 8.1)
Acetic anhydride	108-24-7	203-564-8	> 98.0%	C : R10,R20/22,R34	WEL

3. Hazards Identification



Flammable. Harmful by inhalation and if swallowed. Causes burns.

4. First Aid Measures

Eyes Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION URGENTLY.

Skin Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. If discomfort persists OBTAIN MEDICAL ATTENTION.

Inhalation Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Ingestion If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

5. Fire Fighting Measures

Hazards Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus. Vapour-air mixtures are explosive.

Extinguishing Media Water spray, alcohol resistant foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.

Unsuitable Media Do not use water jet.

6. Accidental Release Measures

Personal Protection	Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so.
Environmental	Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.
Major Spillage	Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.
Minor Spillage	Contain and absorb on inert material. Neutralise spill with soda ash, lime, calcium carbonate or sodium bicarbonate. Wash to drain with copious amounts of water.

7. Storage & Handling

Handling Precautions	Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing. Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.
Storage Conditions	Well ventilated, cool, dry storage . Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use.

8.1 Workplace Exposure Limits

Workplace Exposure Limits	Long Term (8hr TWA):	0.5000 ppm	2.500 mg m ⁻³
	Short Term (15min Period):	2.000 ppm	10.00 mg m ⁻³

8.2 Personal Protection

Respiratory	Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.
Hands	Use PVC gauntlets.
Eyes	Use chemical full face shield.
Skin	Wear PVC oversuit.

9. Physical & Chemical Properties

Appearance	Clear colourless liquid.
Odour	Sharp vinegary odour and burning taste.
pH	Not available
Boiling point	139.6 °C
Melting point	73.1- °C
Flash point	54.0 °C(Closed cup)
Upper Flammable Limit	10.1 %
Lower Flammable Limit	2.7 %
Auto Ignition	330.0 °C
Explosive properties	Moderate/severe in confined spaces.
Oxidising Properties	No.
Vapour Pressure	5.3 mbar @ 20 C
Relative Density	1.0810
Water Solubility	Completely soluble in water but reacts vigorously with much evolution of heat and fumes.

10. Stability & Reactivity

Chemical Stability	Stable under normal conditions
Conditions to Avoid	Hot surfaces, naked flames or other sources of ignition.
Materials to Avoid	Water. Alkalis.
Hazardous Decomposition Products	None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

11. Toxicological Information

Eyes	The vapour is irritating to the eyes. The liquid and solutions will cause severe burns. Damage can range from severe irritation and corneal scarring to permanent blindness.
Skin	The liquid and solutions will cause severe burns. Repeated exposure may cause dermatitis.
LD50 Skin	Rabbit 4000 mg/kg
Ingest	Causes severe corrosion of the mouth, throat and gastro-intestinal tract.
LD50 Ingest	Oral Rat 1780 mg/Kg
Inhalation	Exposure to vapour concentrations above the occupational exposure limits will produce severe irritation of the eyes, nose, throat and respiratory tract. High concentrations of vapour may seriously damage the membranes lining the nose, throat and upper respiratory tract.
Carcinogenicity	Not considered to be a carcinogen.
Mutagenicity	Not considered to be a mutagen.
Reproductive Effects	None identified.
Other Information	The irritant effect provides warning that control of exposure is needed.

12. Ecological

Readily biodegradable in both fresh and salt water. Bio-oxidation as a % of Theoretical O₂ Demand

13. Disposal Considerations

Disposal Methods	Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of into water courses or sewerage systems due to high risk of explosion.
Contaminated Packaging	Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

14. Transport Information

Proper Shipping Name	Acetic Anhydride
UN Number	1715
UN Classification	8 Corrosive
Subsidiary Risk	3 Flammable liquid
Flash Point	54.0 °C(Closed cup)
Packing Group	II
Transport Category	2
Marine pollutant	No
ADR Hazard ID	83



15. Regulatory Information

Labelling	Corrosive.
Classification	

Label Symbols	C	
---------------	---	--

Risk & safety Phrases	Flammable. Harmful by inhalation and if swallowed. Causes burns. Keep locked up and out of reach of children. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing, gloves and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label).
EEC Number	203-564-8

16. Other Information

Document Information This document has been prepared in accordance with directive 88/379/EEC.

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment.

Revision Date: 20/07/07.

Data reviewed and PDF file generated: 17/03/10.

Copyright 2010 Camlab Limited.