1. Identification

Product Code 1110532

Product Name NITRIC ACID 70% w/w tech.

Molecular Formula HNO₃ =63.01

CAS Number 7697-37-2

Supplier:



CAMLAB LIMITED

Norman Way Industrial Estate Over Cambridge England

CB4 5WE

Phone 01954 233110 Fax 01954 233101

Emergency Telephone 08:00-17:00 01954 233110

24hr 112

(Have this document to hand)

2. Composition

Component	CAS No	EEC No	Conc w/w	Classification & Risk Phrases	Exp (See 8.1)
Nitric acid	7697-37-2	231-714-2	70.0%	O C : R8,R35	WEL

3. Hazards Identification





Contact with combustible material may cause fire. Causes severe burns.

4. First Aid Measures

Eyes Irrigate thoroughly with plenty of water for at least 10 minutes, holding the

eye open. OBTAIN MEDICAL ATTENTION URGENTLY.

Skin Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash

before re-use. OBTAIN MEDICAL ATTENTION URGENTLY.

Inhalation Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give

oxygen if available. If breathing stops or shows signs of failing, apply artificial

resuscitation. If conscious place in a sitting position. OBTAIN MEDICAL ATTENTION URGENTLY.

Ingestion If conscious give plenty of water to drink. Do not induce vomiting. If unconscious place in

the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

5. Fire Fighting Measures

Hazards Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-

fighters should wear protective clothing and breathing apparatus. May evolve toxic fumes if

involved in a fire.

Extinguishing

Media

Consider what other flammable materials are present and act accordingly.

Unsuitable Media Nothing specified.

6. Accidental Release Measures

Personal Avoid breathing vapour. Use approved personal protective equipment. Evacuate area

Protection immediately. Do not allow general use of area until it is safe to do so.

Environmental Keep non-neutralised material out of sewers, storm drains, surface waters and soil. Notify

the Environmental Agency and local Environmental Health Officer if major spillage occurs.

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal.

Wash area down with copious amounts of water.

Minor Spillage Neutralise spill with soda ash, lime, calcium carbonate or sodium bicarbonate. Wash area

down with copious amounts of water.

7. Storage & Handling

Handling Precautions Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate

clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended

limits.

Storage Conditions Well ventilated, cool, dry storage . Keep well separated from acids, metals, explosives,

organic peroxides and ignitable materials.

8.1 Workplace Exposure Limits

Workplace Exposure Limits Long Term (8hr TWA): 2.000 ppm 5.200 mg m-3 Short Term (15min Period): 4.000 ppm 10.00 mg m-3

8.2 Personal Protection

Respiratory Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits.

If not, use a well maintained chemical cartridge respirator, or use self contained

breathing apparatus.

Hands Use PVC gauntlets.

Eyes Use chemical splash proof glasses or goggles.

Skin If skin contact or contamination of clothing is likely, protective clothing must be worn.

9. Physical & Chemical Properties

Appearance Clear colourless to pale yellow fuming liquid.

Odour Suffocating and irritating.

pH 1 @ 20 °C
Boiling point 122.0 °C
Melting point 42.0- °C
Flash point Not available
Upper Flammable Limit Not available
Lower Flammable Limit Not available
Auto Ignition Not available

Explosive properties No.

Oxidising Properties A strong oxidising agent.

Vapour Presure 9 mmHg @ 20 C Relative Density 1.4200 °C

Water Solubility Completely soluble in water with moderate increase in temperature.

10. Stability & Reactivity

Chemical Stability Stable under normal conditions

Conditions to Avoid No specific conditions.

Materials to Avoid Reducing agents. Alkalis. Many organic compounds. Combustible materials.

Hazardous Not flammable but will assist a fire, producing irritant and toxic fumes of oxides of

Decomposition Products nitrogen.

11. Toxicological Information

Eyes The vapour is be extremely irritating to eyes and can cause chemical eye burns. Damage can

range from severe irritation and corneal scarring to permanent blindness.

Skin Both the vapour and liquid will, cause severe burns. The liquid or concentrated vapour will

cause immediate severe and penetrating burns. Concentrated solutions will cause deep burns and yellow discolouration of the skin. Dilute solutions will be irritating to the skin.

LD50 Skin Not available

Ingestion may prove fatal. Ingestion will cause severe mouth burns, and if swallowed

extensive damage to the oesophagus. Symptoms may include salivation, thirst, difficulty in

swallowing, pain, shock and vomiting.

LD50 Ingest Not available

Inhalation Exposure to vapour concentrations above the occupational exposure limits will produce

irritation of the eyes, nose, throat and respiratory tract. Prolonged exposure to vapour concentrations above the occupational exposure limits may have serious effects with initially no pathological signs. Further exposure may cause acute pulmonary oedema often

with a serious outcome.

Carcinogenicity Not considered to be a carcinogen.

Mutagenicity No information is available.

Reproductive Effects None identified.

12. Ecological

Acidic, nutrient for undesirable algae.

13. Disposal Considerations

Disposal Methods

Dilute in a large excess of water and carefully neutralise with soda ash, then wash to drain with copious amounts of water.

Contaminated Packaging Use a licensed waste disposer. Wash out containers with water.

14. Transport Information

Proper Shipping Name Nitric Acid UN Number 2031

UN Classification 8 Corrosive
Subsidiary Risk 5.1 Oxidising agent
Flash Point Not available

Packing Group II
Transport Category 2
Marine pollutant No
ADR Hazard ID 80





15. Regulatory Information

Labelling Oxidising, Corrosive.

Classification

Label Symbols







Risk & safety Phrases

Contact with combustible material may cause fire. Causes severe burns. Keep locked up and out of reach of children. Do not breath vapour. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing. In case of accident or if you feel unwell, seek medical advice immediately (show the label).

EEC Number 231-714-2

16. Other Information

Document Information

This document has been prepared in accordance with directive 88/379/EEC.

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment.

Revision Date: 22/04/09.

Data reviewed and PDF file generated: 17/03/10.

Copyright 2010 Camlab Limited.