Camlab Limited – Material Safety Data Sheet

1111612

1. Identification

Product Code	1111612
Product Name	ACETIC ACID 1.0M (N/1) A.R.
CAS Number	64-19-7
Supplier:	CAMLAB LIMITED
camlab	Norman Way Industrial Estate Over Cambridge England CB4 5WE
Phone	01954 233110
Fax	01954 233101
Emergency Telephone	08:00-17:00 01954 233110 24hr 112 (Have this document to hand)

2. Composition

Component	CAS No	EEC No	Conc w/w	Classification & Risk Phrases	Exp (See 8.1)
Acetic acid	64-19-7	200-580-7	6.0%	R10,R35	WEL

3. Hazards Identification

Not considered harmful

4. First Aid M	leasures
Eyes	Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION URGENTLY.
Skin	Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. If discomfort persists OBTAIN MEDICAL ATTENTION.
Inhalation	Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If discomfort persists OBTAIN MEDICAL ATTENTION.
Ingestion	If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

5. Fire Fighting N	leasures
Hazards	Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire- fighters should wear protective clothing and breathing apparatus.
Extinguishing Media	Water spray, alcohol resistant foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.
Unsuitable Media	Do not use water jet.

6. Accidental Release Measures

Personal Protection Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so.

6. Accidental Release Measures (continued)		
Enviromental	Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.	
Major Spillage	Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.	
Minor Spillage	Wash area down with copious amounts of water.	

7. Storage & Handling

Handling PrecautionsAvoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate
clothing.Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended
limits.Storage ConditionsWell ventilated, cool, dry storage .

8.1 Workplace Exposure Limits

Component	CAS No	Workplace Expos	sure Limits	Maximum Exp	posure Limits
		Long Term	Short Term	Long Term	Short Term
		ppm mg m–3	ppm mg m–3	ppm mg m–3	ppm mg m-3
Acetic acid	64-19-7	10.00 25.00	15.00 37.00		

8.2 Personal Protection		
Respiratory	Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.	
Hands	Use nitrile gloves or PVC gauntlets.	
Eyes	Use chemical full face shield.	
Skin	Wear PVC oversuit.	

9. Physical & Chemical Properties

Appearance	Clear colourless liquid.
Odour	Sharp vinegary odour and burning taste.
рH	5 @ 20 °C
Boiling point	Not available
Melting point	Not available
Flash point	Not available
Upper Flammable Limit	Not available
Lower Flammable Limit	Not available
Auto Ignition	Not available
Explosive properties	No.
Oxidising Properties	No.
Vapour Presure	Not available
Relative Density	1.0600 °C
Water Solubility	Completely soluble in water.

10. Stability & Reactivity

Chemical Stability	Stable under normal conditions
Conditions to Avoid	No specific conditions.
Materials to Avoid	Hydrogen peroxide, chromium trioxide and potassium permanganate. Potassium t-butoxide. Alkalis.
Hazardous Decomposition Products	None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

11. Toxicological	Information
Eyes	Both the vapour and liquid will, be irritating to the eyes.
Skin	Both the vapour and liquid will, be irritating to the skin.
LD50 Skin	Not available
Ingest	Causes severe corrosion of the mouth, throat and gastro-intestinal tract.
LD50 Ingest	Not available
Inhalation	High concentrations of vapour will produce severe irritation of the eyes, nose, throat and respiratory tract.
Carcinogenicity	Not considered to be a carcinogen.
Mutagenicity	Not considered to be a mutagen.
Reproductive Effects	None identified.
Other Information	The irritant effect provides warning that control of exposure is needed. 10ppm is the threshold for irritation with severe irritation occurring above 25ppm.

12. Ecological

Readily bio-degraded in the environment. Slightly toxic to aquatic species but is unlikely to bioaccumulate.

13. Disposal Considerations

Disposal Methods

Dilute in a large excess of water and carefully neutralise with soda ash, then wash to drain with copious amounts of water.

Contaminated Packaging Wash out containers with water. Use a licensed waste disposer.

14. Transport Inf Proper Shipping Name	Non-restricted
UN Number	Non-restricted
UN Classification	None
Subsidiary Risk	None
Flash Point	Not available
Packing Group	None
Transport Category	None
Marine pollutant	No
ADR Hazard ID	Non-restricted

15. Regulatory Information		
Labelling Classification	None	
Label Symbols	None	
Risk & safety Phrases	Keep out of reach of children. After contact with skin, wash immediately with plenty of water.	
EEC Number	200-580-7	

16. Other Information

Document Information This document has been prepared in accordance with directive 88/379/EEC.

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment.

16. Other Information (continued)

Revision Date: 15/09/00. Data reviewed and PDF file generated: 17/03/10. Copyright 2010 Camlab Limited.