

Camlab Limited – Material Safety Data Sheet


1. Identification

Product Code CC/1258-CA

Product Name **METHYL ORANGE SOLUTION**

CAS Number **Mixture**

Supplier: **CAMLAB LIMITED**



**Norman Way Industrial Estate
Over
Cambridge
England
CB4 5WE**

Phone **01954 233110**

Fax **01954 233101**

Emergency Telephone **08:00-17:00 01954 233110**
24hr 112
(Have this document to hand)

2. Composition

Component	CAS No	EEC No	Conc w/w	Classification & Risk Phrases	Exp (See 8.1)
Propan-2-ol	67-63-0	200-661-7	20.0%	R11,R36,R67	WEL

3. Hazards Identification

Flammable.

4. First Aid Measures

Eyes Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION.

Skin Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. If discomfort persists OBTAIN MEDICAL ATTENTION.

Inhalation Remove from exposure. Keep warm and at rest.

Ingestion If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

5. Fire Fighting Measures

Hazards Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus. May evolve toxic fumes if involved in a fire.

Extinguishing Media Water spray, alcohol resistant foam, dry powder or carbon dioxide.

Unsuitable Media Nothing specified.

6. Accidental Release Measures

Personal Protection Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so. Beware : vapour is heavier than air and will tend to accumulate at low spots.

6. Accidental Release Measures (continued)

Environmental	Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.
Major Spillage	Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.
Minor Spillage	Wash area down with copious amounts of water.

7. Storage & Handling

Handling Precautions	Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing. Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.
Storage Conditions	Well ventilated, cool, dry storage .

8.1 Workplace Exposure Limits

Component	CAS No	Workplace Exposure Limits				Maximum Exposure Limits			
		Long Term		Short Term		Long Term		Short Term	
		ppm	mg m ⁻³	ppm	mg m ⁻³	ppm	mg m ⁻³	ppm	mg m ⁻³
Propan-2-ol	67-63-0	400.0	999.0	500.0	1250	-	-	-	-

8.2 Personal Protection

Respiratory	Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.
Hands	Use solvent resistant gloves.
Eyes	Use chemical splash proof glasses or goggles.
Skin	Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

9. Physical & Chemical Properties

Appearance	Clear orange solution.
Odour	Fresh and characteristic.
pH	7 @ 20 °C
Boiling point	Aqueous solution
Melting point	11.0- °CAqueous solution
Flash point	27.0 °C(Closed cup)
Upper Flammable Limit	Aqueous solution
Lower Flammable Limit	Not available
Auto Ignition	Not available
Explosive properties	Slight.
Oxidising Properties	No.
Vapour Pressure	59 mmHg @ 20,C
Relative Density	0.9700 °C
Water Solubility	Completely miscible in water.

10. Stability & Reactivity

Chemical Stability	Stable under normal conditions
Conditions to Avoid	Hot surfaces, naked flames or other sources of ignition.
Materials to Avoid	Strong oxidising agents.
Hazardous Decomposition Products	May produce hazardous fumes if involved in a fire.

11. Toxicological Information

Eyes	The liquid will cause conjunctival irritation and corneal damage. High concentrations of vapour may be irritating to the eyes.
Skin	Repeated or prolonged contact may defat the skin producing irritation and dermatitis. Unlikely to be absorbed across the skin in harmful amounts.
LD50 Skin	Not available
Ingest	Low order of acute toxicity.
LD50 Ingest	Not available
Inhalation	Exposure to vapour concentrations above the occupational exposure limits may produce irritation of the eyes and respiratory tract.
Carcinogenicity	Not considered to be a carcinogen.
Mutagenicity	Not considered to be a mutagen.
Reproductive Effects	Not considered to be a mutagen.

12. Ecological

Readily bio-degraded in the environment.

13. Disposal Considerations

Disposal Methods	Dispose of in a licensed incinerator for organic solvents.
Contaminated Packaging	Wash out containers with water. Use a licensed waste disposer.

14. Transport Information

Proper Shipping Name	Flammable Liquid, N.O.S. (Methyl Orange Solution)
UN Number	1993
UN Classification	3 Flammable liquid
Subsidiary Risk	None
Flash Point	27.0 °C(Closed cup)
Packing Group	III
Transport Category	2
Marine pollutant	No
ADR Hazard ID	60



15. Regulatory Information

Labelling	Flammable.
Classification	
Label Symbols	None
Risk & safety Phrases	Flammable.
EEC Number	Not available

16. Other Information

Document Information	This document has been prepared in accordance with directive 88/379/EEC. The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. Revision Date: 18/01/10. Data reviewed and PDF file generated: 17/03/10. Copyright 2010 Camlab Limited.
----------------------	---