

Camlab Limited – Material Safety Data Sheet


1. Identification

Product Code CC/0358-CO

Product Name **HYDROBROMIC ACID 50% w/w pure**

Molecular Formula **HBr =80.91**

CAS Number **10035-10-6**

Supplier: **CAMLAB LIMITED**
**Norman Way Industrial Estate
Over
Cambridge
England
CB4 5WE**


Phone **01954 233110**
Fax **01954 233101**

Emergency Telephone **08:00-17:00 01954 233110**
24hr 112
(Have this document to hand)

2. Composition

Component	CAS No	EEC No	Conc w/w	Classification & Risk Phrases	Exp (See 8.1)
Hydrobromic acid	10035-10-6	233-113-0	50.0%	C : R34,R37	WEL

3. Hazards Identification



Causes burns. Irritating to respiratory system.

4. First Aid Measures

Eyes Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION URGENTLY.

Skin Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. OBTAIN MEDICAL ATTENTION.

Inhalation Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If conscious place in a sitting position. OBTAIN MEDICAL ATTENTION URGENTLY.

Ingestion If conscious give plenty of water to drink. Do not induce vomiting. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

5. Fire Fighting Measures

Hazards Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus. May evolve toxic fumes if involved in a fire.

Extinguishing Media Consider what other flammable materials are present and act accordingly.

Unsuitable Media Dry chemical powder.

6. Accidental Release Measures

Personal Protection	Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so.
Environmental	Keep non-neutralised material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.
Major Spillage	Neutralise spill with soda ash, lime, calcium carbonate or sodium bicarbonate. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.
Minor Spillage	Neutralise spill with soda ash, lime, calcium carbonate or sodium bicarbonate. Wash area down with copious amounts of water.

7. Storage & Handling

Handling Precautions	Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing. Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.
Storage Conditions	Well ventilated, cool, dry storage .

8.1 Workplace Exposure Limits

Workplace Exposure Limits	Long Term (8hr TWA):	-	ppm	-	mg m-3
	Short Term (15min Period):	3.000	ppm	10.00	mg m-3

8.2 Personal Protection

Respiratory	Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge respirator, or use self contained breathing apparatus.
Hands	Use PVC gauntlets.
Eyes	Use chemical splash proof glasses or goggles.
Skin	If skin contact or contamination of clothing is likely, protective clothing must be worn.

9. Physical & Chemical Properties

Appearance	Pale yellow fuming liquid.
Odour	Pungent and intensely irritating.
pH	1 @ 20 °C
Boiling point	126.0 °C
Melting point	Not available
Flash point	Not available
Upper Flammable Limit	Not available
Lower Flammable Limit	Not available
Auto Ignition	Not available
Explosive properties	No.
Oxidising Properties	No.
Vapour Pressure	8 mbar @ 20 C
Relative Density	1.4900 °C
Water Solubility	Completely soluble in water with moderate increase in temperature.

10. Stability & Reactivity

Chemical Stability	Stable under normal conditions
Conditions to Avoid	No specific conditions.
Materials to Avoid	Alkalis. Strong oxidising agents. Reacts with most metals to produce extremely flammable hydrogen gas. Ammonia, fluorine, iron oxide fume, ozone and selenium dioxide.
Hazardous Decomposition Products	May decompose to emit toxic and irritant fumes of hydrogen bromide.

11. Toxicological Information

Eyes	The vapour is be extremely irritating to eyes and can cause chemical eye burns. Damage can range from severe irritation and corneal scarring to permanent blindness.
Skin	The vapour will cause severe burns. Severe ulceration and scarring may occur in serious cases. The liquid is irritating to the skin. Repeated exposure may cause dermatitis.
LD50 Skin	Not available
Ingest	Ingestion will cause severe mouth burns, and if swallowed extensive damage to the oesophagus. Symptoms may include salivation, thirst, difficulty in swallowing, pain, shock and vomiting.
LD50 Ingest	Not available
Inhalation	Exposure to vapour concentrations above the occupational exposure limits will produce irritation of the eyes, nose, throat and respiratory tract. High concentrations of vapour will seriously damage the membranes lining the nose, throat and upper respiratory tract.
Carcinogenicity	Not considered to be a carcinogen.
Mutagenicity	Not considered to be a mutagen.
Reproductive Effects	None identified.

12. Ecological

Neutralised material presents no specific environmental hazard.

13. Disposal Considerations

Disposal Methods	Dispose of in a licensed incinerator. Never dispose of into water courses or sewerage systems.
Contaminated Packaging	Use a licensed waste disposer. Carefully neutralise with a weak sodium hydroxide solution then wash out thoroughly with water.


14. Transport Information

Proper Shipping Name	Hydrobromic acid
UN Number	1788
UN Classification	8 Corrosive
Subsidiary Risk	None
Flash Point	Not available
Packing Group	II
Transport Category	2
Marine pollutant	No
ADR Hazard ID	80



15. Regulatory Information

Labelling	Corrosive.
Classification	

Label Symbols	C	
---------------	---	-------------------------------------------------------------------------------------

Risk & safety Phrases	Causes burns. Irritating to respiratory system. Keep locked up and out of reach of children. Keep container tightly closed and in a well ventilated place. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of accident or if you feel unwell, seek medical advice immediately (show the label).
-----------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

EEC Number	233-113-0
------------	-----------

16. Other Information

Document Information This document has been prepared in accordance with directive 88/379/EEC.

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment.

Revision Date: 19/11/03.

Data reviewed and PDF file generated: 19/07/07.

Copyright 2007 Camlab Limited.