



*Monocular microscope, 600x,
achromatic objectives*

| | | |
|---|--|-----------------------|
| Observation Method - Transmitted Light | Brightfield | Yes |
| | Simple polarized light | As optional |
| Main Body | Type | Upright |
| | Construction material | Aluminum die-cast |
| | Trasportation handle | Yes |
| Head | Type | Monocular |
| | Inclination | 45° |
| | 360° rotating | Yes |
| | Fixing screw for eyepieces | Yes |
| | Tube inner diameter (mm) | 23 |
| Eyepieces | Field number (mm) | 18 |
| | Magnification | 10x |
| | Pointer | As optional |
| | Micrometric scale | As optional |
| Nosepiece | Positions | Quadruple |
| | Reversed | Yes |
| | Bi-directional | Yes |
| | Rotation on ball bearings | Yes |
| | Objective thread | RMS |
| Objectives | Optical system | 160 |
| | Anti-fungus treatment | Yes |
| | Parfocal distance (mm) | 35 |
| | Standard magnifications | 40x-600x |
| | Type | Achromatic |
| | | 4x/0.10, W.D. 10.6 mm |
| | | 10x/0.25, W.D. 7.0 mm |
| | 40x/0.65, W.D. 0.5 mm | |
| | 60x/0.85, W.D. 0.13 mm | |
| Stage | Type | Double layer |
| | Dimensions (mm) | 125x125 |
| | Moving mechanism | Rack and pinion |
| | Moving range (mm) | 62x24 |
| | Material | Anti-scratch painting |
| | Specimen holder | Yes |
| | Slide number | 1 |
| | X-Y Vernier scale | Yes |
| | Vernier scale accuracy (mm) | 0.1 |
| Condenser - Single Position | Type | Abbe |
| | Numerical aperture (N.A.) | 1.25 |
| | Diaphragms | Iris |
| | Focusable | By rotation |
| Focusing System | Type | Coaxial coarse & fine |
| | Coarse total travel (mm) | 23 |
| | Fine total travel (per single rotation) (mm) | 1.2 |
| | Fine graduations | 100 |
| | Fine resolution (µm) | 12 |
| | Upper stop to prevent contact | Yes |

| | | |
|---------------------------------|-------------------------|----------|
| Transmitted Illumination | Type | LED |
| | Light source power (W) | 1 |
| | Brightness control | Manual |
| | Lifetime (hours) | > 65,000 |
| | Temperature (K) | 6,300 |
| | Max. required power (W) | 1.5 |

| | | |
|--|------------------------------------|-------------------------|
| Power Supply for Transmitted Illumination | Type | External |
| | Microscope connector | Jack, 2.1 mm |
| | Power plug type | Multi-plug (EU, UK, US) |
| | Input voltage | 100/240 Vac, 50/60 Hz |
| | Output voltage | 5 Vdc 500 mA |
| | Rechargeable batteries | Yes |
| | Battery type | Ni-MH (3x, AAA size) |
| | Working time of batteries (hours) | 4 |
| | Charging time of batteries (hours) | 8 |

| | | |
|-----------------------------|-------------|--------------------------------|
| Accessories Included | Dust cover | Yes |
| | User Manual | Digital version (downloadable) |

| | | |
|---------------------------|-------------|-----|
| Product Dimensions | Height (mm) | 330 |
| | Width (mm) | 135 |
| | Depth (mm) | 235 |

| | | |
|-----------------------|------|-----|
| Product Weight | (kg) | 2.7 |
|-----------------------|------|-----|